

# TERMINATION STUD SYSTEM

TEL. 800.346.4296 FAX. 800.441.4296

**Attachment:** Our Termination Stud System is very simple to setup and install. Simply drill holes in your verticals for the cable to pass through. The termination cap pulls against the last vertical to tension. Countersunk type termination studs use standard 82 degree countersink for a flush fit.

**Examples of Applications:** This system is very good for retrofitting existing rails to meet current codes. Termination Studs are a very cost effective and clean method of installing and tensioning cable assemblies because they can be used with any type or style of post. The termination shaft on the turnbuckle is available in different lengths to pass through various post sizes.

**Other Information:** Our standard termination stud turnbuckle can be used for up to a 2" OD post on a level or angle run. Rods are also available for 6" and 12" posts.

Get more information now at [www.haynlines.com](http://www.haynlines.com)

## HAYN LINES STAINLESS STEEL CABLE SYSTEMS

Hayn Enterprises, LLC


51 Inwood Road

Rocky Hill, CT USA

SHEET:TS05FA



### TERMINATION STUD HARDWARE



#### Termination Stud Turnbuckle

	Thread (b)	Body L (d)	Open L (e)	Closed L (e)	Catalog #
swage	1/4-28	4-1/4"	10-1/4"	7-1/8"	6TT3TS
	1/4-28	4-1/4"	10-1/2"	7-1/2"	6TT4TS
	1/4-28	4-1/4"	10-1/2"	7-1/2"	6TT5TS
	5/16-24	4-3/4"	10-3/4"	8"	8TT5TS
	5/16-24	4-3/4"	10-3/4"	8-1/8"	8TT6TS
crimp	1/4-28	4-1/4"	10-1/4"	7-1/8"	6TT3TSC
	1/4-28	4-1/4"	10-1/2"	7-1/2"	6TT5TSC

#### common specs

Cap Size (a)	Wire Size (c)
9/16"	1/8"
9/16"	5/32"
9/16"	3/16"
9/16"	3/16"
9/16"	1/4"
3/4"	1/4"
9/16"	1/8"
9/16"	3/16"

#### Termination Stud

Catalog #
TS3
TS4
TS5
TS5
TS6
TS61
TS3C
TS5C



### COUNTERSUNK TERMINATION STUD HARDWARE



#### Countersunk Termination Stud Turnbuckle

	Thread (b)	Body L (d)	Open L (e)	Closed L (e)	Catalog #
swage	1/4-28	4-1/4"	11"	8"	6TT3CTS
	1/4-28	4-1/4"	11-1/8"	8-1/8"	6TT4CTS
	1/4-28	4-1/4"	11-1/4"	8-1/4"	6TT5CTS
crimp	1/4-28	4-1/4"	11-1/4"	8-1/4"	6TT3CTSC
	1/4-28	4-1/4"	11-1/4"	8-1/4"	6TT5CTSC

#### common specs

Cap Size (a)	Wire Size (c)
9/16"	1/8"
9/16"	5/32"
9/16"	3/16"
9/16"	1/8"
9/16"	3/16"

#### Countersunk Termination Stud

Catalog #
CTS3
CTS4
CTS5
CTS3C
CTS5C